



Fashion Floors

A COMPLETE
LINE OF
FLOOR TILE IN
DESIGNER
COLORS AND
STYLES



THE FLINTKOTE COMPANY

Manufacturer of America's Broadest Line of Building Products



TYPES:

Flexachrome® vinyl-asbestos

The finest all-purpose flooring ever developed. The first vinyl tile to be produced commercially. Its smart appearance, yet rugged characteristics, makes it ideal for almost any area whether over wood, concrete or steel.

This beautiful floor is greaseproof and highly resistant to most acids, alkalis and other chemicals. Flexachrome can pay for itself in maintenance savings alone. Waxing is not necessary. Dirt can't penetrate its smooth, dense surface. Choice of 7 handsome styles.

Tile-Tex® asphalt-asbestos

Attractive colors and styles, durability coupled with low cost keep Tile-Tex Asphalt-Asbestos Tile a leader in the flooring field for practically any area not exposed to grease and oil.

flexible vinyl

The floor for those who want the finest. Luxurious Terrazzo, Roman Marble and Plaza Styles. Strong and versatile with built-in lasting beauty. Their lovely colors will enrich any setting.

rubber

Quiet and comfort under foot. Its up to the minute colors blend in with any setting. Flintkote Rubber Tile is highly resistant to most oils, greases and solvents commonly found around the home. Not available in the 13 Western States except in car-load quantities shipped direct from the factory.

SUPER TUFF-TEX® greaseproof-asbestos

Developed specifically for industrial areas, and proven over the years in many of the nation's biggest plants. Tuff-Tex is the original greaseproof tile. It has no equal. This heavy-duty floor tile withstands greases, oils and plant traffic. Maintenance is very economical, particularly when compared to other types of plant floors. The light, attractive colors blend in with styling in today's modern plants.

SELECTOR

USE	TYPE TILE	TILE STYLE	PAGE
RESIDENTIAL AND LIGHT COMMERCIAL	<i>Flexachrome</i> vinyl-asbestos	Skytrail®	4
		FlexGold*	4
		Woodflex*	4
		Holiday®	5
		Korkolor®	5
		Flexweave*	5
		Marbleized	6-7
	<i>Tile-TeX</i> asphalt-asbestos	Marbleized	8
		Texwood*	9
		Korkolor	9
		Holiday	9
		Texweave*	9
	rubber	Marbleized	11
	flexible vinyl	Terrazzo	12
		Roman Marble*	13
		Plaza*	13
COMMERCIAL AND INSTITUTIONAL	<i>Flexachrome</i> vinyl-asbestos	Woodflex	4
		Marbleized	6-7
	<i>Tile-TeX</i> asphalt-asbestos	Marbleized	8
		Texwood*	9
	rubber	Marbleized	11
	flexible vinyl	Terrazzo	12
		Roman Marble	13
		Plaza	13
INDUSTRIAL	<i>Flexachrome</i> vinyl-asbestos	Marbleized	6-7
	SUPER TUFF-TEX greaseproof-asbestos	Marbleized	10

*Trademark of The Flintkote Company




Flexachrome

VINYL-ASBESTOS FLOOR TILE

Skytrail

this exclusive, delicate and wisp-like pattern lends itself to many interesting designs.




FS-105 Celestial



FS-101 Vega



FS-106 Lyra




FS-115 Explorer



FS-120 Adara



FS-118 Corona




FS-121 Hydra




FS-119 Antares

FlexGold


bonanza colors that provide special dramatic effects and bring new beauty to any setting.



FG-1849 Yukon




FG-1870 Dawson




FG-1852 Eldorado



FG-1872 Comstock



FG-1850 Gold Coast



FG-1871 Fort Knox

Woodflex

the rich wood grain and color go clear through each tile.



WF-20 Cherry



WF-21 Oak



WF-22 Driftwood




WF-23 Maple


Six handsome styles created for the home and light commercial areas—in popular decorator colors that blend in well with all interiors. The easy-to-live with qualities of Flexachrome make this vinyl asbestos tile as practical as it is beautiful. Use it over wood sub-floors or concrete slabs in the kitchen, basement playroom, anywhere. Formulated to meet the requirements of Federal Specifications L-T-751—Type I and L-T-00345. Available in size 9" x 9" in 1/16" thickness (Woodflex in .080 and 1/8" thicknesses also).

Holiday


this festive terrazzo pattern is a cinch to keep looking clean and new.




FH-711 Santiago




FH-701 Quebec




FH-743 Melbourne




FH-746 Daytona



FH-744 San Juan




FH-745 Martinique




FH-742 Catalina

Korkolor


the luxurious look of cork in carefree Flexachrome.



FK-50 Cintra




FK-51 Alhandra




FK-52 Narvao

Flexweave


these subtle tone-on-tone colors give the look of wall-to-wall luxury.




FW-1 Edinburgh




FW-4 Dundee




FW-6 Banff




FW-9 Chalet




FW-2 Perth



FW-7 Montgomery



FW-5 Huntly



FW-8 Orleans

Flexachrome

VINYL-ASBESTOS FLOOR TILE (CONTINUED)

Marbleized style

the beauty won't wear off
because the marbleization and color
go all the way through.



A floor for all to enjoy.



F-754 Toast



F-63 Theatre



F-740 Painted Desert



F-752 Raspberry



F-753 Cream



F-751 Honey



F-738 Grand Canyon




F-739 Blue Heaven




F-756 Malt



Design possibilities are unlimited.



F-757 Oyster




F-737 White City



F-755 Olive

The finest all-purpose flooring ever developed. Excellent throughout schools, offices and industrial areas as well as the home. Easy and economical to maintain. Use it on, above or below grade over wood, concrete or steel. Formulated to meet the rigid requirements of Federal Specifications L-T-751—Type I and L-T-00345.


Standard size 9" x 9" in 1/16", .080 or 1/8" thicknesses; 3/16" thickness on special order. (1/16" thickness designed specially for the home and light commercial areas only.) 18" x 24" border tile made in solid Black in .080 and 1/8" thicknesses only.




F-733 Showroom



F-734 Gun Club




F-716 Palace



F-722 Conservatory




F-94 Club House




F-64 White House



F-727 Patio



F-90 Cloister




F-81 Bermuda




F-302 Embassy




F-723 Chateau




F-61 Salon



F-304 Niagara



F-93 Resort



F-726 Ivory Tower




F-4 Chalk



F-1 Ebony

FEATURE STRIPS


Come in 24" lengths in 1", 2" and 3" widths in .080 and 1/8" thicknesses.



F-3 Cardinal Red



F-4 Chalk White



F-1 Ebony Black



F-7 Sunshine Yellow



F-11 Oriental Green




F-9 Rose Pink

Tile-Text


ASPHALT-ASBESTOS FLOOR TILE

Marbleized

The color and marbleizing go clear through each tile for lasting beauty.




D-021 McIntosh




C-760 Bisque




B-207 Viking



D-074 Billow




C-773 Burnt Umber




C-768 Tucson




B-221 Interlude




D-064 Serenade




C-759 Meadow



C-763 Jubilee




C-762 Daybreak



D-054 Sylvan




B-202 Norman




D-023 Dune




C-775 Navarro



C-714 Killarney



C-772 Sundown



C-713 Tango

FEATURE STRIPS

24" lengths. 1", 2" or 3" widths. 1/8" or 3/16" thicknesses.



C-59 Juniper




A-21 Black



D-101 Cherry



D-134 Snow



A-27 Mulberry

Five attractive styles in economical Asphalt tile. And Tile-Tex is strengthened with Asbestos, nature's permanent fiber. It's ideal for all residential and light commercial areas not exposed to greases and oils—on, above and below grade over wood or concrete. The "clear through" Marbleized Style decoration has long made it a favorite in schools and other hard-wear areas. Formulated to meet Federal Specification SS-T-306b.

Available in size 9" x 9" in 1/8" thickness; Marbleized Style and border tile also made in 3/16" thickness. 18" x 24" border tile made in solid Black and Mulberry only.

Texwood

the friendly,
rich look of
wood.




WA-10 Oak




WA-11 Mahogany

Korkolor


the warm,
luxurious look
of cork.



K-11 Barcelona




K-12 Lisbon




K-13 Portugal

Holiday


the festive
look gives a "lift"
to any room.




B-820 Reno



D-841 Monte Carlo




B-821 Fiesta




C-833 Picacho

Texweave


the carpet-like
look with subtle
tone-on-tone.



TW-3 Stratford



TW-4 Bristol



TW-2 Sydney



TW-7 Heights

SUPER TUFF-TEX

GREASEPROOF-ASBESTOS FLOOR TILE

Tuff-Tex is the original greaseproof tile. It was developed for industrial areas, and proven in many of the nation's biggest plants. Super Tuff-Tex is even tougher and more handsome.

Marbleized style


Plant traffic won't wear its beauty off for the colors and veining go all the way through the tile.




ST-1990 Birmingham



ST-1968 Detroit




ST-1920 Cleveland




ST-1959 Akron



ST-1910 Scranton



ST-1921 Vernon



ST-1930 Pittsburgh



ST-1962 Chicago

Super Tuff-Tex takes greases, oils and an amazing amount of truck abuse. It's strengthened with Asbestos—nature's permanent fiber. The close-textured surface makes maintenance easy and economical, particularly when compared to other types of plant floors. The pleasant colors will keep employees' morale high.

Installed on, above or below grade over wood or concrete. Super Tuff-Tex is formulated to meet the rigid requirements of Federal Specification SS-T-307—both Class 1 and 2. Standard size is 9"x9" in $\frac{1}{8}$ " and $\frac{3}{16}$ " thicknesses; $\frac{1}{4}$ " thickness and solid color available on special order.



Super Tuff-Tex's light, bright colors blend in well with today's modern plants, as shown above in The Bendix Corporation plant in Holmdel, N. J.

Rubber

FLOOR TILE


The rich colors combine wonderfully with smart decorative trends. Use on and above grade over wood or concrete with recommended Flintkote adhesives. Formulated to meet Federal Specification ZZ-T-301a. Made in size 9"x9" in .080 and 1/8" thicknesses. Not available in the 13 Western States except in carload quantities shipped direct from factory.

Marbleized style

The beautiful decorator shades will not wear off because the color and veining go all the way through.




R-815 Tahiti




R-805 Azores



R-816 Cebu




R-811 Bahama




R-806 Fiji




R-804 Java



R-812 Canary




R-807 Zanzibar




R-814 Ceylon



R-801 Bali



R-810 Samoa



R-809 Hawaii



R-803 Trinidad



R-808 Borneo



R-802 Jamaica



R-813 Sumatra

Flexible Vinyl


FLOOR TILE

Terrazzo style


In size 9" x 9" in .080 and
 $\frac{1}{8}$ " thicknesses. .080 shown below,
 $\frac{1}{8}$ " has heavier, bolder pattern.



VT-615 Bologna



VT-601 Vercelli




VT-605 Naples




VT-611 Ancona




VT-616 Catania




VT-603 Ferrara



VT-606 Pisa




VT-612 La Spezia




VT-613 Turin




VT-602 Florence




VT-609 Venice




VT-610 Rome




VT-604 Leghorn



VT-607 Bari



VT-614 Messina



VT-608 Milan

For those who want the finest, here are three floors of distinction. So luxurious, yet so practical with all the wonderful, carefree qualities of vinyl—dirt repellent, stain resistant and greaseproof. Their lasting, built-in beauty will enrich and blend with any setting. Takes little more than a damp cloth to keep them attractive. Use any one of these three styles on or above grade, over wood or concrete sub-floors with the recommended Flintkote adhesives.

Formulated to meet Federal Specifications L-T-751—Type II and L-F-00450.

Roman Marble

The beauty of ancient marble with semi-translucent color magic. In size 12" x 12" in $\frac{1}{8}$ " thickness.



VM-1001 Rosa Pink



VM-1002 Miele Honey



VM-1003 Bianca White



VM-1004 Nero Black



VM-1005 Verde Green

Plaza

Delicately muted, pearly colors with a deep dimensional effect. In size 12" x 12" in .080 gauge.



P-1104 Gray Agate



P-1101 White Alabaster



P-1105 Taupe Garnet



P-1106 Olive Jade



P-1102 Cream Opal



P-1103 Beige Onyx

Installations, Adhesives, and Other Products

SUB-FLOOR	Concrete On or Below Grade	Concrete Above Grade†	Double Constructed Wood Floors* Top Surface Tongue and Groove Boards Not Over ¾" Wide	Double Constructed Wood Floors* Top Surface Plywood	Single Construction Wood Floors* ¾" Plywood	Magnesite Above grade only	Terrazzo, Marble and Ceramic
FLEXACHROME** VINYL-ASBESTOS	GF-8 Fast-Set	Fast-Set GF-8	Fast-Set GF-8	Fast-set GF-8	Fast-Set GF-8	GF-8	Fast-Set GF-8
TILE-TEX ASPHALT ASBESTOS	GF-8 Fast-Set	Fast-Set GF-8 Bondcote #5	Fast-Set GF-8 Bondcote #5	Fast-set GF-8 Bondcote #5	Fast-Set GF-8 Bondcote #5	GF-8	Fast-Set GF-8
SUPER TUFF-TEX GREASEPROOF ASBESTOS	GF-8 Fast-Set	Fast-Set GF-8	Fast-Set GF-8	Fast-Set GF-8	Fast-Set GF-8	GF-8	Fast-Set GF-8
FLEXIBLE VINYL FLOOR TILE	Tile-TEX Epoxy Adhesive	Tile-TEX Rubber and Flexible Vinyl Tile Cement Fast-Set	Tile-TEX Rubber and Flexible Vinyl Tile Cement Fast-Set	Tile-TEX Rubber and Flexible Vinyl Tile Cement Fast-Set	Tile-TEX Rubber and Flexible Vinyl Tile Cement Fast-Set	Treat like concrete ... see column 1 and 2.	Treat like concrete ... see column 1 and 2.
RUBBER FLOOR TILE	Tile-TEX Epoxy Adhesive	Tile-TEX Rubber and Flexible Vinyl Tile Cement	Tile-TEX Rubber and Flexible Vinyl Tile Cement	Tile-TEX Rubber and Flexible Vinyl Tile Cement	Tile-TEX Rubber and Flexible Vinyl Tile Cement	Treat like concrete ... see column 1 and 2.	Treat like concrete ... see column 1 and 2.
PREPARATION OF UNDER FLOOR	Do not use felt. Dusty concrete should be primed with Tile-TEX Floor Primer to assist binding. Mechanically remove paint, varnish, wax, old coverings. Smooth with Tile-TEX latex type underlay- ment as required. Radiant heating in- stallations shall be so controlled that temperature of the concrete slab shall never be in excess of 85° F.	Dusty concrete should be primed with Tile-TEX Floor Primer when Fast- Set or Bondcote #5 is the adhesive to assist binding. Me- chanically remove old paint, varnish, wax, old coverings. Smooth with Tile- TEX latex underlay- ment. Radiant heating in- stallations shall be so controlled that temperature of the concrete slab shall be in excess of 85° F.	Nail loose boards. Sand to a smooth surface. Use Tile- TEX Latex Under- layment to smooth, level and feather- edge rough spots. Cement down flooring felt with linoleum paste. Double wooden floors that cannot be sanded smooth, or otherwise in bad shape, should be covered with ¼" plywood or hardboard (un- tempered) under- layment board.	Plywood shall be ¼" minimum thickness over tongue and groove sub-floor boards 4" wide or under, ¾" minimum over wider boards. Joist spacing shall be not over 16" between centers. Felt is optional.	Must be ¾" or heavier plywood over joists spaced not over 16" cen- ters. Solid blocking un- der joists at right angles to joists is required.	Do not install tile over Magnesite in contact with earth.	Sand or scrub with strong solution of trisodium phos- phate and flush with clean water.

*All wood floors must be firm, smooth and have no springiness. When directly over the earth they must have good ventilation between them and the earth to prevent buckling and rotting.

Plywood shall be Interior Type Underlayment Grade C (plugged)—D or better or any sanded Exterior Grade Type. Install smooth side up. Use Exterior Grade in bathrooms or other areas where dampness exists. Plywood should be nailed with flat head ringed or screw-type nails 1¼" or longer 3" apart along joists, 6" elsewhere. Nail heads shall be flush or counter sunk no more than 1/32".

**For 1/16" Flexachrome, use trowel with small notches to prevent trowel mark show-through, or, if Fast-Set is used, it may also be applied with a roller or brush.

†Where air space is less than 3 feet and without proper heat and ventilation, the concrete slab considered on grade.

On steel remove any paint or other types of coating. Use Latex underlayment if necessary to smooth floor.

Flintkote has a complete line of adhesives. They are designed for the job and developed through years of experience in installation methods and in the manufacture of flooring materials. Use only the type of Flintkote adhesive specified. The Flintkote Company cannot assume responsibility where other than Flintkote Products are used. Additional installation information is given in the specifications on the back cover of this brochure.

To preserve the beauty of your floors and to take the drudgery out of floor care, use Tile-Tex Floor Finish, Cleaner, and Tile Stain Remover.

Old Asphalt Tile or Linoleum	Plywood or Hard-board Underlayment*	Tile-Tex Latex Underlayment
Fast-set	Fast-Set GF-8	Fast-Set GF-8
Fast-Set	Fast-Set GF-8 Bondcote #5	Fast-Set GF-8 Bondcote #5
Fast-Set	Fast-Set GF-8-	Fast-Set GF-8
above grade, Tile-Tex Rubber and Flexible Vinyl Tile Cement or Fast-Set.	Tile-Tex Rubber and Flexible Vinyl Tile Cement	Treat like concrete ... see column 1 and 2.
If above grade, Tile-Tex Rubber and Flexible Vinyl Tile Cement.	Tile-Tex Rubber and Flexible Vinyl Tile Cement	Treat like concrete ... see column 1 and 2.
Removal of old asphalt tile is preferable. Satisfactory results may be obtained over old asphalt tile on suspended floors by careful preparation. Remove all old wax or other coating. Fill all cracks. A skim coat of Latex Underlayment is advisable to prevent spaces between old tile from showing through.	Nail loose boards. Sand to a smooth surface. Use Tile-Tex Latex Underlayment to smooth, level and feather-edge rough spots. Cement down flooring felt with linoleum paste. See Column 3 on double constructed wood floors.	Tile-Tex Latex Underlayment described at lower right.



Contains rubber latex. Non-flammable. Non-toxic. Apply with brush, roller or trowel. Lay tile almost immediately or up to many hours later.



Cut-back type. The best all-purpose adhesive for asphalt and vinyl-asbestos tile over concrete. Has high resistance to moisture.



A superior clay emulsion asphalt which can be used as both a tile adhesive or an underlayment base.



A light-colored, non-staining resin base adhesive. Waterproof. Has exceptionally long open time of 30 minutes.



Mix this liquid with powder from 40-lb bag just prior to use. Provides a thin, smooth, tough, but flexible base for all types of floor covering. Trowel applied.



For installing Rubber or Flexible Vinyl Tile on concrete in contact with ground. 2 part can. Mix Component "A" with "B" just prior to use.

RUBBER SET-ON COVE BASE




48" lengths, 4" and 6" heights, in Black or Brown.

A waterproof cement that gives a strong and immediate bond for all vinyl and rubber cove bases.



VINYL REDUCING STRIP



Continuous lengths in Black, 1" width, 1/16", 1/8" and 3/16" thicknesses.

A slip-resistant, self-polishing floor finish for all types of resilient flooring.



A neutral, non-toxic detergent. Effective even in cold water. Rinses without streaking.



Removes adhesive spots, rubber burns and many stains from vinyl asbestos and asphalt floors.



ARCHITECTURAL SPECIFICATIONS

MATERIAL—Shall be (TILE-TEX Asphalt-Asbestos Floor Tile in Marbleized, Texwood, Korkolor, Holiday or Texweave styles) (FLEXACHROME Vinyl-Asbestos Floor Tile in Marbleized, Skytrail, Holiday, Korkolor, Flexweave, Woodflex or FlexGold styles) (SUPER TUFF-TEX Greaseproof-Asbestos Floor Tile) (FLINTKOTE Flexible Vinyl Floor Tile in Terrazzo, Roman Marble or Plaza styles) (FLINTKOTE Rubber Floor Tile) as sold by the Flooring and Adhesive Division of The Flintkote Company.

Asphalt-Asbestos Tile shall conform to the requirements of Federal Specification SS-T-306b; Greaseproof-Asbestos Tile shall meet requirements of Federal Specification SS-T-307; Vinyl-Asbestos Tile shall meet requirements of Federal Specification L-T-751—Type I and L-T-00345; Flexible Vinyl Tile shall meet requirements of Federal Specification L-T-751—Type II and L-F-00450; Rubber Tile shall meet requirements of Federal Specification ZZ-T-301a.

(a) For areas subject to greases, oils and food, specify greaseproof materials (FLEXACHROME Vinyl-Asbestos Tile) (SUPER TUFF-TEX) and/or (FLINTKOTE Flexible Vinyl Tile). FLINTKOTE Rubber Tile can be used under mild conditions.

SUB FLOORS—Concrete Sub-floors, whether suspended, on grade, or below grade, should be smooth, dry, and protected from moisture infiltration, free from surface irregularities and foreign matter. All previous floor covering or paint should be removed, except on suspended floors. Sub-floors should be of the proper strength and density to withstand the type and weight of traffic to which the finished resilient floor is to be subjected.

Wood Sub-floors shall be smooth, firm, without springiness and of sufficient strength to carry intended loads without deflection.

Double constructed wood floors with tongue and groove surface boards not over $3\frac{1}{4}$ " wide that are smooth and in good shape should have 15 lb. saturated flooring felt cemented down first with linoleum paste before tile is applied. Rough, double wooden floors or floors having top boards over $3\frac{1}{4}$ " wide should be covered first with $\frac{1}{4}$ " plywood or underlayment board.

Single wood floors shall be covered with $\frac{3}{8}$ " or heavier plywood unless subflooring is tongue and groove boards under 4" wide when $\frac{1}{4}$ " plywood or underlayment board can be used. Underlayment board and plywood do not require felt.

Single plywood floors are satisfactory for resilient tile if plywood is $\frac{7}{8}$ " minimum on joists not over 16" between centers with solid blocking under plywood joints.

SIZE AND GAUGE—TILE-TEX Asphalt Tile is available in size 9" x 9" in $\frac{1}{8}$ " thickness in all styles; Marbleized style also in $\frac{3}{16}$ " thickness. FLEXACHROME Vinyl-Asbestos Tile comes in size 9" x 9" in $\frac{1}{16}$ " thickness in all styles; Marbleized and Woodflex styles also in .080 and $\frac{1}{8}$ " thickness. SUPER TUFF-TEX Greaseproof-Asbestos Tile is made in size 9" x 9" in $\frac{1}{8}$ " and $\frac{3}{16}$ " thicknesses. FLINTKOTE Flexible Vinyl Tile is available in size 9" x 9" in .080 and $\frac{1}{8}$ " thicknesses in Terrazzo style, in size 12" x 12" in .080 gauge in Plaza style, in size 12" x 12" in $\frac{1}{8}$ " thickness in Roman Marble Style. FLINTKOTE Rubber Tile comes in size 9" x 9" in .080 and $\frac{1}{8}$ " thicknesses.

BASE—Where Cove Base is desired to finish or trim at the base of wall, use Tile-Text Rubber Set-On Cove Base (4" or 6").

APPLICATION—Installation of Tile-Text products shall not begin until the work of all other trades, particularly painting and plastering, has been completed.

All rooms and sub-floors shall be maintained at a minimum of 70°F for at least 48 hours before, during and 48 hours after application of tile.

Installation of Tile-Text products shall be by an approved Tile-Text flooring contractor in strict accordance with the Tile-Text specifications.

CEMENTS—Tile-Text GF-8 Cement or Fast-Set Adhesive are the recommended adhesives for installing all Tile-Text products, except Flexible Vinyl Tile and Rubber Tile, on finished concrete slabs in accordance with the standards of the Portland Cement Association. They should be used for below grade, on grade and suspended concrete sub-floors which are free of moisture. No further preparations are necessary, such as priming.

Porous, dusty concrete floors should be primed with Tile-Text's Floor Primer.

Over wood sub-floors having linoleum-pasted saturated felt, GF-8 Cement or Fast-Set Adhesive shall be used to bond all Tile-Text products except Flexible Vinyl Tile and Rubber Tile.

Flintkote Rubber Tile and Flintkote Flexible Vinyl Tile can be installed in above grade areas over wood or concrete with Tile-Text Rubber and Flexible Vinyl Tile Cement (Flintkote Flexible Vinyl Tile can also be installed in these areas with Fast-Set adhesive); over grade level concrete sub-floors with Tile-Text Epoxy Adhesive.

GUARANTEE—Flexachrome Vinyl-Asbestos Tile, Tile-Text Asphalt-Asbestos Tile, Super Tuff-Text Greaseproof-Asbestos Tile, Flintkote Rubber Tile and Flintkote Flexible Vinyl Tile shall be guaranteed by The Flintkote Company against defects in its floor tiles and by the Tile-Text Contractor against defects in workmanship for a period of one year from date of completion.

For detailed information refer to the nearest Office listed below.

THE FLINTKOTE COMPANY

FLOORING AND ADHESIVE DIVISION

30 ROCKEFELLER PLAZA

NEW YORK 20, N. Y.

Chicago Heights, Illinois
1232 McKinley Avenue

Los Angeles 54, California
P. O. Box 2218 Terminal Annex

New Orleans 12, Louisiana
1221 Carondelet Building



Manufacturer of America's Broadest Line of Building Products



ARCHITECTURAL SPECIFICATIONS

MATERIAL—Shall be (TILE-TEX Asphalt-Asbestos Floor Tile in Meshlined Pattern 17 1/2" x 17 1/2")

Digitized by



ASSOCIATION
FOR
PRESERVATION
TECHNOLOGY,
INTERNATIONAL
www.apti.org

BUILDING
TECHNOLOGY
HERITAGE
LIBRARY

<https://archive.org/details/buildingtechnologyheritagelibrary>

From the collection of:

Mike Jackson, FAIA

Flintkote Rubber Tile and Flintkote Flexible Vinyl Tile shall be guaranteed by The Flintkote Company against defects in its floor tiles and by the Tile-Text Contractor against defects in workmanship for a period of one year from date of completion.

For detailed information refer to the nearest Office listed below.

THE FLINTKOTE COMPANY FLOORING AND ADHESIVE DIVISION

30 ROCKEFELLER PLAZA

NEW YORK 20, N. Y.

Chicago Heights, Illinois
1232 McKinley Avenue

Los Angeles 54, California
P. O. Box 2218 Terminal Annex

New Orleans 12, Louisiana
1221 Carondelet Building



Manufacturer of America's Broadest Line of Building Products

Holiday
Corkolor,
FLINTKOTE
Tile) as

aseproof-
all meet
all meet
require-

E Vinyl-
e can be

smooth,
previous
e proper
oor is to

ntended

that are
m paste
ould be

l groove
ard and
over 16"

l styles;
n 1/16"
FF-TEX
le Vinyl
0 gauge
omes in

in Cove

es, par-
during

ordance

stalling
ordance
i grade
essary,

hall be

r wood
an also
ile-TEX

grease-

